



# Part Number: 9410

300V PLTC, (1 pr) 16 AWG (19x29) TC, PVC/PVC, CMG

# Request Sample

## **Product Description**

One 16 AWG pair stranded (19x29) tinned copper conductors, PVC insulation, PVC jacket.

# **Technical Specifications**

### **Physical Characteristics (Overall)**

# Conductor

AWG	Stranding	Material	No. of Pairs
16	19x29	TC - Tinned Copper	1
Condu	ctor Count:		2
Total	Number of Pa	nirs:	1
Total	Number of Tr	iads:	N/A
Condu	ictor Size:		16 AWG

### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.017 in

### Color Chart

Number	Color
1	Black & Red

### **Outer Shield Material**



### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.260 in	0.037 in	Yes

# **Construction and Dimensions**

	LEGEND: BELDEN 9410 E34972 1PR16 (UL) CMG 105C OR PLTC OR ITC SUN RES OR AWM 2464 80C 300V OR C(UL) CMGFT4 IEEE 1202 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET
--	---

#### **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR 4.2 Ohm/1000ft

#### Capacitance



### Inductance

Nominal Inductance

# Voltage



# **Temperature Range**

UL Temp Rating:	80°C
Operating Temp Range:	-30°C To +105°C

# **Mechanical Characteristics**

Bulk Cable Weight:	34 lbs/1000ft
Max Recommended Pulling Tension:	40 lbs
Min Bend Radius/Minor Axis:	2.52 in

### **Standards**

NEC/(UL) Specification:	CMG, ITC-ER, PLTC-ER
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2464 (300 V 80°C)

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

# Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 Vertical Tray Flame Test
CSA Flammability:	FT4
IEEE Flammability:	1202
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):

### **Part Number**

### Variants

Item #	Color	Footnote
9410 0601000	Chrome	С
9410 0602500	Chrome	Z
9410 060U1000	Chrome	С
9410 060U500	Chrome	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

#### © 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.