

• Power is provided via USB connection. If additional power is needed, connect a 5V 2A external power

# supply (sold separately) that uses a 3.5 x 1.3 x 8 mm output plug with positive tip and negative sleeve. USB 3.1 Gen 2 (10 Gbps) SATA SSD/HDD to USB-C Enclosure Adapter with UASP Support, Metal Housing, Thunderbolt<sup>™</sup> 3 Compatible

# MODEL NUMBER: U457-025-SATAG2











Slim aluminum enclosure connects a SATA SSD or HDD to your computer's USB-C or Thunderbolt<sup>™</sup> 3 port and performs fast file transfers at USB 3.1 Gen 2 speeds. UASP-enabled for 70% more speed with UASP host controller.

## Description

The U457-025-SATAG2 USB 3.1 Gen 2 (10 Gbps) SATA SSD/HDD to USB-C Enclosure Adapter lets you connect a high-performance SATA solid state drive (SSD) or hard disk drive (HDD) to a computer or laptop with a USB-C or Thunderbolt<sup>™</sup> 3 port. Not only does it support USB 3.1 Gen 2 data transfer rates up to 10 Gbps, but it reads data up to 70 percent faster and writes up to 40 percent faster when connected to a UASP-enabled host controller.

Recommended for storing and sharing large files, such as photos, music and video files, the U457-025-SATAG2 accepts 2.5-inch SATA drives up to 2 TB. You can access data on an older SATA drive, or use a new SATA drive for additional storage space. The adapter is plug-and-play, so no software, drivers or external power supply is required, and it is backward compatible with previous USB generations. A white LED indicates data is being read or written.

The durable, slim aluminum housing stores conveniently in a backpack or laptop bag for use anywhere. The housing is ventilated to keep the interior cool and help prevent data from being corrupted.

In most cases, the USB connection provides enough power. In case additional power is needed, connect an external power supply (sold separately) between the unit's DC-In port and an AC outlet. The U457-025-SATAG2 is compatible with 5V 2A power supplies that use a 3.5 x 1.3 x 8 mm output plug with a positive tip and negative sleeve.

# Highlights

- Compatible with 2.5 in. SATA SSDs and HDDs up to 2 TB
- Supports USB 3.1 Gen 2 data transfer rates up to 10 Gbps
- Works up to 70% faster when connected to UASP host controller
- Vented aluminum housing keeps drive cool to prevent data corruption
- Plug-and-play—no software, drivers or external power supply needed

### **System Requirements**

- Computer with USB-C or Thunderbolt<sup>™</sup> 3 port (USB 3.1 Gen 2 port required for maximum speed)
- 2.5 in. SATA SSD or HDD (9.5 mm max height)
- UASP-enabled host controller required for UASP performance
- Compatible with all USBenabled operating systems

## **Package Includes**

- U457-025-SATAG2 USB 3.1
  Gen 2 SATA SSD/HDD to USB-C Enclosure Adapter
- USB 3.1 Gen 2 USB-C cable (M/M), 2 ft.
- (4) Drive mount screws
- (4) Enclosure screws
- Screwdriver
- Rubber feet
- Owner's manual



USB Type-C<sup>™</sup> and USB-C<sup>™</sup> are trademarks of USB Implementers Forum

# Features

#### Connects an Internal SATA Drive to Your Computer's USB-C or Thunderbolt™ 3Port

- · Recommended for storing and sharing large photo, music and video files
- Supports USB 3.1 Gen 2 data transfer rates up to 10 Gbps
- Features UASP for performance up to 70% faster when connected to UASP-enabled host controller
- Compatible with all USB-enabled operating systems

#### Compatible with 2.5 in. SATA Drives Up to 2 TB

- Accepts SATA III, II and I SSDs and HDDs
- Will support higher-capacity drives when available
- Backward compatible with previous USB generations
- · White LED indicates drive data is being read or written

#### **Designed for Immediate Use**

- Plug and play—no software, drivers or external power supply needed
- · Durable slim aluminum housing perfectly sized for backpack or laptop bag
- Ventilated housing keeps interior cool and helps prevent data from being corrupted
- USB 3.1 Gen 2 Type-C cable included

#### **Power Provided via USB Connection**

- · Accepts user-supplied external power supply in case additional power is needed
- Compatible with 5V 2A power supplies that use 3.5 x 1.3 x 8 mm output plug with positive tip and negative sleeve

# **Specifications**

OVERVIEW		
UPC Code	037332202444	
Drives Supported	2.5" HDD and SSD	
Technology	SATA/eSATA; USB (all versions); USB 3.1 (Gen 2)	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240	
External Power Supply Input Specs (V / Hz / A)	100-240 / 50/60Hz / 0.4A	



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

External Power Supply Output Specs (V / A)	5V / 2A	
External Power Supply DC Barrel Connector Specs	OD: 3.5 x 1.3 x 8mm, Positive Pin, Negative Sleeve	
Bus Powered	Yes	
USER INTERFACE, ALERTS & CON	ITROLS	
LED Indicators	White (Power, Data)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	1.890 x 7.130 x 5.040	
Shipping Dimensions (hwd / cm)	4.80 x 18.11 x 12.80	
Shipping Weight (lbs.)	0.3300	
Shipping Weight (kg)	0.15	
Unit Packaging Type	Box	
Unit Dimensions (hwd / in.)	0.8 x 4.9 x 3.1	
Unit Dimensions (hwd / cm)	2 x 12.5 x 7.8	
Unit Weight (lbs.)	0.33	
Unit Weight (kg)	0.15	
Material of Construction	Aluminum	
Color	Black	
ENVIRONMENTAL		
Operating Temperature Range	50 to 122 F (10 to 50 C)	
Storage Temperature Range	32 to 149 F (0 to 65 C)	
Relative Humidity	10% to 80% RH, Non-Condensing	
BTUs	17.1 BTU/Hr	
Power Consumption (Watts)	5	
CONNECTIONS		
Ports	1	
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	22 PIN SATA + POWER (FEMALE)	
Connector Plating	Nickel	
Contact Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.1 Gen 2 (up to 10 Gbps)	



Driver Required	No	
UASP Support	Yes	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, ROHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies