

## Planar Cores (9578100502)



Part Number: 9578100502

78 ER CORE SET

Planar EE and EI cores, with their low profile are suitable for board level installation allowing assembly without the need for plastic coilformers and can also allow windings integrated into multi-level PCBs. Planar ER cores with their low mass and low profile are suitable for Surface Mount installations in low power filter and transformer applications.

 $\Box$ Planar EE, ER and EI cores can be supplied with the center post gapped to a mechanical dimension, or an  $A_L$  value.

Weight: 0.7 (g)

| Dim   | mm       | mm tol      | nominal inch        | inch misc.        |  |   |
|-------|----------|-------------|---------------------|-------------------|--|---|
| A     | 9.35     | ± 0.30      | 0.368               |                   | Chart Legend  El/ A : Core Constant, l <sub>e</sub> : Effective Path  Length, A <sub>e</sub> : Effective Cross- Sectional Area,  Effective Core Volume | V |
| В     | 2.45     | ± 0.15      | 0.096               |                   |  |   |
| C     | 4.9      | ± 0.20      | 0.193               | _                 |  |   |
| D     | 1.68     | ± 0.11      | 0.066               | _                 |  |   |
| Е     | 7.65     | $\pm 0.30$  | 0.301               |                   |  |   |
| F     | 3.4      | ± 0.15      | 0.134               |                   |  |   |
| G     | 7        | min         | 0.276               | min               |  |   |
| Expla | nation o | of Part Nur | mbers: Digits 1 & 2 | = product class a | $A_L$ : Inductance Factor and 3 & 4 = material grade.  |   |

| Electrical P          | Electrical Properties |  |  |  |  |
|-----------------------|-----------------------|--|--|--|--|
| $A_L(nH)$             | 900 ±25%              |  |  |  |  |
| Ae(cm <sup>2</sup> )  | 0.0893                |  |  |  |  |
| $\Sigma l/A(cm^{-1})$ | 15.2                  |  |  |  |  |
| l <sub>e</sub> (cm)   | 1.36                  |  |  |  |  |
| $V_e(cm^3)$           | 0.122                 |  |  |  |  |
| $A_{min}(cm^2)$       | 0.076                 |  |  |  |  |

A<sub>L</sub> value is measured at 1 kHz, B < 10 gauss.

Fair- Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288

888-324-7748 • 845-895-2055

Fax: 845-895-2629

ferrites@fair- rite.com

www.fair- rite.com