

Specification Control Drawing

a) Part as supplied

302W2**



b) Part after unrestricted recovery.



DIMENSI	ONS (<u>in mi</u>	llime	tres)	•							
		ŀ	-1	`	J	Ρ	R	S	Т	V	ΗW	JW
Part	Size	Min	Мах	Min	Мах	±10%	±10%	±10%	±10%	±10%	±20%	±20%
Number		a	b	а	b	b	b	b	b	b	b	b
302W233	(B)	29	22	10	3.0	65	42	9.5	2.0	5.0	2.0	2.0
302W244	(C)	35	27	14	6.0	70	42	13	2.0	5.0	2.0	2.0

Copyright(!)

The copyright in this drawing is the property of Tyco Electronics UK Ltd. The drawing is issued on the conduction that it is not copied, reproduced on disclosed to a third party, either in whole or in part without the prior written consent of Tyco Electronics UK Ltd.



lss.	Date	E.C.R. No.	Details of Change
1 2 3 4	**** **** February 2001	**** **** ****	J min was 12, J max was 6 J min was 12, J max was 6 233 5 was 9.5, 244 5 was 13 Redrawn

(Ordering Information)



(COMPATIBILITY CHART)

MATERIAL DASH NUMBER	MATERIAL DESCRIPTION	COATING SLASH NUMBER
-3	POLYOLEFIN, SEMI-RIGID	/42 ,/86
-4	POLYOLEFIN, FLEXIBLE	/42 ,/86
-25	ELASTOMER, FLUID RESISTANT	/86,/225
-130	POLYOLEFIN, COMMERCIAL FLEXIBLE	/42

AS SUPPLIED DIMENSIONS ARE FOR UNCOATED PARTS, WHEN COATING IS ADDED, ENTRY DIAMETERS WILL REDUCE BY 1.5mm MAX.

Raychem Wire & Harness a Division of Tyco Electronics Faraday Road, Swindon, Wiltshire, England. SN3 5JA Telephone: (01793) 528171 Fax: 572516 Raychem Wire & Harness a Division of Tyco Electronics 300, Constitution Drive, Menlo Park, California 94025-1164, USA Telephone (650) 361-3333 Fax: (650) 361-5579