

Search 



All 3M Products Innovation About 3M

United States  [Change](#)

Industrial Adhesives & Tapes

Products | Applications | Industries | Capabilities | Support

Where to Buy

[United States](#) > [All 3M Products](#) > [Manufacturing and Industry](#) > [Industrial Adhesives & Tapes](#) > [3M Tapes & 3M Adhesives](#) > [Fasteners](#) > [3M™ Dual Lock™ Reclosable Fasteners](#) > 3M™ Dual Lock™ Reclosable Fastener SJ3542 170 Black, 2 in x 50 yd 0.23 in (5.8 mm), 1 per case Bulk

3M™ Dual Lock™ Reclosable Fastener SJ3542 170 Black, 2 in x 50 yd 0.23 in (5.8 mm), 1 per case Bulk

3M ID 70070458370 UPC# 00021200873409 Part Number SJ3542 3M Product Number SJ3542

[Print](#)



[View All Images](#)

3M™ Dual Lock™ Reclosable Fastener SJ3542 has a rubber based adhesive on the back of a black, polypropylene reclosable fastener. 3M™ Dual Lock™ Reclosable Fastener SJ3542 has a 400 stems per square inch with a 0.23 inch engaged thickness. The closure life is 1,000 times.

- A black fastener with mushroom shaped stems that is backed with a rubber based pressure sensitive adhesive.
- Type 170 stem density polyolefin fastener which mates to Type 250 or 400.
- Designed to bond to many plastics, powder coated paints and other low surface energy materials.
- General Industrial, Packaging, Point of Purchase Displays, Exhibits, Electronics, Construction, Furniture and Maintenance, Repair and Operations (MRO).
- Attach Doors, Access Panels, Signs and Display Components.

Need Help?

[Share](#)

Questions? We can help
[Contact Us](#)

[Where to Buy](#)

Like [Sign Up](#) to see what your friends like.

Overview

Documents

3M™ Dual Lock™ Reclosable Fastener SJ3542 has low temperature performance, with a temperature resistance of up to 120 degrees fahrenheit and is for indoor use only. This product is for use with many plastics (acrylic, polycarbonate and AS, powder coated paints and low surface energy materials (polypropylene and polyethylene).

Specifications

Adhesive Type	Rubber
Brand	Dual Lock
Closure Life	1000
Color	Black
Engaged Thickness	0.23 Inch
Flame Retardant	No
Indoor/Outdoor	Indoor
Industries	Construction, Furniture, General Industrial, Retail, MRO, Electronics, Packaging
Length	50 Linear Yard
Length (Metric)	45.72 m
Liner Thickness	5 mil
Liner Type	White Polyolefin
Low Profile	No

Maximum Operating Temperature (Celsius)	49 Degree Celsius
Maximum Operating Temperature (Fahrenheit)	120 Degree Fahrenheit
Product Form	Roll
Stem Density	170
Width	2 Inch
Width (Metric)	50.8 mm

3M: [News](#) | [Careers](#) | [Partners & Suppliers](#) | [Investor Relations](#) | [MSDS Search](#) | [Transport Information Search](#) | [Contact 3M](#)

[Legal Information](#) | [Privacy Policy](#)

© 3M 2014. All Rights Reserved.

