


NOTES: UNLESS OTHERWISE SPECIFIED.

- 1. MATERIAL & FINISH:
- 1.1 BODY: PASSIVATED STAINLESS STEEL
- 1.2 DIELECTRIC: NORYL (POLYPHENYLENE ETHER)
- 1.3 CENTER CONTACT: GOLD PLATED BERYLLIUM COPPER
- 1.4 MOUNTING NUT: PASSIVATED STAINLESS STEEL
- 1.5 LOCKWASHER: NICKEL PLATED BRASS ALLOY
- 2. ELECTRICAL SPECIFICATIONS:
- 2.1 FREQUENCY RANGE: DC 40 GHz
- 2.2 VSWR (MAX): 1.20:1



RECOMMENDED MOUNTING HOLE

EMERSON.	3RD ANGLE PROJECTION	MIDWEST MICROWAVE
Network Power Connectivity Solutions This PROPRIETARY Document is properly of temeston Network. The properly of temeston Network is confidential in nature. In confidential in nature, and issued with the clear understanding that it is permission and is returnable upon demand. INTERPRET DRAWING IN ACCORDANCE WITH ASME YEARSON TO A CONTRACT OF THE NATURE OF THE NA	RoHS2 2011/65/EU	Title: ADAPTER, 2.9mm BULKHEAD JACK TO JACK
	UNLESS OTHERWISE SPECIFIED UNITS: INCH .XX ±.02 .XXX ±.005 ANGLES ±2°	Model No. ADT-2854-FF-29M-02
		A DO NOT SCALE Date: 8/15/2014 Sheet 1 of 1