THERMOFIT • SPECIFICATION CONTROL DRAWING • MOLDED PARTS

NOTES

1. All dimensions are in inches.

2. Dimensions appearing in table are as follows:

a - AS SUPPLIED b - AFTER UNRESTRICTED RECOVERY

3. The following coatings are optional: S-1017 (/42) adhesive and S-1048 (/86) adhesive for -3 or -4 material only

Dimensions appearing in table are for uncoated parts. When coating is added entry diameters will be reduced .06 max.

- Molding ports are optional. When -00 modification number is specified they will be located as shown.
- 5. Weight shown in table of dimensions is based on polyolefin part.

ORDERING INFORMATION

Matl. No.	Description	Raychem RT Spec			
-3	Polyolefin, Semi-Rigid	RT-301			
-4	Polyolefin, Flexible	RT-1304			
-8	Polyolefin, Space	RT-1308			
-25	Elastomer, Semi-Rigid	RT-1325			

Add material dash number as suffix to part number; Example 1 - Order 234A711-3 when polyolefin, semi-rigid is required.

Add coating slash number as suffix to material dash number when coating is required.

Example 2 - Order 234A752-X/42 when S-1017 adhesive is required.

Example 3 - Order 234A732-3-00 when molding ports are required.

.12 DIA. MOLDING PORT

(SEE NOTE A



.18 DIA. MOLDING PORT

(SEE NOTE 4)



AS SUPPLIED



AFTER UNRESTRICTED RECOVERY

If this document is printed it becomes uncontrolled. Check for the latest revision.

TABLE OF DIMENSIONS														
PART NUMBER	⊢ Min a	ל ±5% b	Min	J ±5% b	Min a	K Max b	P ±10% b	R ±10% b		S ±10% b	W ±20% b	X ±20% b	Weight Ibs ±10%	This Boot Fits Cannon
234A711 234A721 234A732 234A742 234A742 234A752	.63 .75 1.15 1.35 1.48	.80 1.11 1.66 2.31 2.28	.63 .75 1.15 1.35 1.48	.42 .42 .42 .42 .54	.63 .75 1.15 1.35 1.48	.16 .21 .25 .31 .36	1.10 1.38 1.87 2.35 2.49	.73 .74 .79 .79 1.04		.50 .50 .56 .56 .69	.04 .04 .04 .04 .04	.12 .12 .12 .12 .12 .12	.0059 .0086 .0143 .0220 .0260	DE-9 DA-15 DB-25 DC-37 DD-50
Raychem E.O. REV DATE Raychem Corporation 300 Constitution Drive Menio Park, CA 94025-1164 415) 361 6055 4			ATE DESC	CRIPTION	drn JC chk'd JS(auth RK auth DD			SUBMINIATURE, 90°, SIDE ENTRY,		7, PART NO. 234A DATE-	234A711 thru 752 F			